

CANNONS



EXM Flange Adapter

NITRO



Adjustable



Smooth Bore

VULCAN



Adjustable



Smooth Bore

SIDEWINDER



Simple Control Options



Position Display



Handheld



Joystick

Nozzles for Every Application



6000-700E



6000-200E

EXM Specifications

Max Flow: 2650 LPM	Control: Joystick or Radio Remote
Inlet: 2.5" NPT	Communication: Digital Radio Frequency
Outlet: 2.5" NHT	Material/Finish: Teflon impregnated, hard anodized Elk-O-Lite
Weight: 8.6Kg	Travel V: -45 to +90 (135) H L175 to R175 (350)
Voltage: 11-27VDC	



Vulcan Specifications

Max. LPM: 4732	Material/Finish: Elk-O-Lite with red urethane enamel
Inlet: 3" Flange	Friction loss: 16 PSI at 1250gmp, 12psi at 1000GPM
Outlet: 2.5" NHT	Travel V: -45 to +90 (135) H360 (Continuous)
Control: Tiller Bar Style	



Sidewinder Specifications

Max. LPM: 1893	Material/Finish: Elk-O-Lite with red urethane enamel
Inlet: 2" NPT	Friction Loss: 26 psi @500gpm / 14 psi@ 350gmp/4 psi@ 200gpm
Outlet: 1.5"NHT	Travel: V-45 to +90 (135) H 360 (Continuous)
Control: Tiller Bar Style	

